

CONTOUR® ELECTROL® Automatic Flectric Projection Screen Model

SPECIFICATION DATA

DA-LITE SCREEN COMPANY, INC.

3100 North Detroit Street Post Office Box 137 Warsaw, Indiana 46581-0137 Phone: 574-267-8101 800-622-3737 Fax: 574-267-7804 www.da-lite.com

e-mail: info@da-lite.com

SUGGESTED SPECIFICATIONS:

_ projection screen(s),

_ (H) x

(W), electrically

operated 120 volt (60 Hz) 2.0 amp. Motor to be mounted inside the roller with a patented noise silencer to be three-wire quick reversal type, oiled for life, with automatic thermal overload cut-out, integral gears, and capacitor. To have preset but adjustable limit switches to automatically stop the picture surface in the "up" and "down" positions. Junction box shall be integrated into the housing making it possible to install the housing and wire to the building's electrical system during construction. The junction box shall contain a four-prong connector that is mounted in the housing for easy plug-in connection to the motorized fabric and roller assembly. The motorized fabric and roller assembly may be installed in the case at the factory or at a later time at the job site. The roller to be of rigid metal, 3" in diameter. Roller mounting brackets to be adjustable to allow centering or offsetting of the screen within the case. Screen case to be a two piece design made of extruded aluminum. Case to be finished in white, lightly textured powder coat. Screen fabric to be a flame retardant and mildew resistant fiberglass with Glass Beaded, Matte White, High Contrast Matte White, Video Spectra 1.5, or High Power® picture surface with black masking borders standard. Bottom of fabric shall be formed into a pocket holding a 3/6" metal rod. Screen to include a three-position control switch and cover plate. Screen to be listed by Underwriters' Laboratories.

Matte White: Horizontal seam required when both dimensions exceed 12'.

(jr)



Glass Beaded: Horizontal seam required when both dimensions exceed 8'.

Video Spectra 1.5 and High Contrast Matte White: Available in sizes where both dimensions do not exceed 8'. **High Power®:** Available in sizes up to 9' x 12'. Horizontal seam required when both dimensions exceed 6'.

VIDEO FORMAT DIMENSIONS

Viewing Area		Nominal Diagonal		Overall Length of Case		Approx. Ship. Wt.	
In.	Cm	In.	Cm	In.	Cm	Lbs.	Kg
43" x 57"	109 x 145	72"	183	693/4"	177	44	20.0
50" x 67"	127 x 170	84"	213	793/4"	203	49	22.2
57" x 77"	145 x 196	96"	244	93³/₄"	238	57	25.8
60" x 80"	152 x 203	100"	254	93³/₄"	238	57	25.8
69" x 92"	175 x 234	120"	305	1053/4"	269	64	29.0
87" x 116"	221 x 295	150"	381	1293/4"	330	87	39.5
105" x 140"	267 x 356	180"	457	153³/₄"	391	97	44.0
120" x 160"	305 x 406	200"	508	173³/₄"	441	109	49.4

HDTV FORMAT DIMENSIONS

Viewing Area		Nominal Diagonal		Overall Length of Case		Approx. Ship. Wt.	
In.	Cm	In.	Cm	ln.	Cm	Lbs.	Kg
45" x 80"	114 x 203	92"	234	933/4"	238	57	25.8
52" x 92"	132 x 234	106"	269	1053/4"	269	62	28.1
54" x 96"	137 x 244	110"	279	109³/₄"	279	63	28.6
58" x 104"	147 x 264	119"	302	1173/4"	299	69	31.3
65" x 116"	165 x 295	133"	338	1293/4"	330	83	37.6
78" x 139"	198 x 353	159"	404	1533/4"	391	96	43.5

DIMENSIONS

		DIMILI	1310113		
Sizes		Overall Length of Case		Approx. Ship. Wt.	
HxW	Cm	In.	Cm	Lbs.	Kg
50" x 50"	127 x 127	593/4"	152	39	17.7
60" x 60"	152 x 152	693/4"	177	45	20.4
70" x 70"	178 x 178	793/4"	203	49	22.2
84" x 84"	213 x 213	933/4"	238	58	26.3
6' x 8'	183 x 244	1053/4"	269	64	29.0
8' x 8'	244 x 244	1053/4"	269	66	29.9
7' x 9'	213 x 274	1173/4"	299	70	31.8
9' x 9'	274 x 274	1173/4"	299	75	34.0
8' x 10'	244 x 305	1293/4"	330	87	39.5
10' x 10'	305 x 305	1293/4"	330	89	40.4
9' x 12'	274 x 366	1533/4"	391	97	44.0
12' x 12'	366 x 366	153³/₄"	391	98	44.5

Overall case length dimensions ±1/4".

Detail dimensional drawings, wiring diagrams and installation instructions available upon request.

Specifications subject to change without notice.

Custom formats and sizes available upon request.

 Optional Accessories: Black "Extra Drop" to lower picture area more than normal. Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. White "Extra Drop" to lower picture area more than normal. Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. Supervises Phone: Supplier Date: 	or:
Matte White ☐ High Contrast Matte White ☐ Glass Beaded ☐ Video Spectra 1.5 ☐ High Power® Optional Accessories: ☐ Black "Extra Drop" to lower picture area more than normal.	or:
Matte White ☐ High Contrast Matte White ☐ Glass Beaded ☐ Video Spectra 1.5 ☐ High Power* Optional Accessories: ☐ Black "Extra Drop" to lower picture area more than normal.	pr:
High Power® Optional Accessories: Black "Extra Drop" to lower picture area more than normal. Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. White "Extra Drop" to lower picture area more than normal. Maximum total drop 13' (396 Cm) including picture area more than normal. Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. No borders (Black masking borders standard). Single Motor Low Voltage Control (LVC) – external. Single Motor Low Voltage Control (LVC) – built-in. Wireless Remote Control for LVC. Radio Frequency Remote Silent Motor for sizes up to 9'x12'. Silent Motor with Integrated LVC for sizes up to 9'x12'. Key Locking Cover Plate for 120 V Switch or LVC. Rey Operated Switch for 120 V only (Note: Cannot be used Architec Phone: Contrac: Phone: Supervis	pr:
Optional Accessories: ☐ Black "Extra Drop" to lower picture area more than normal. Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. ☐ White "Extra Drop" to lower picture area more than normal. Maximum total drop 13' (396 Cm) including picture area more than normal. Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. ☐ No borders (Black masking borders standard). ☐ Single Motor Low Voltage Control (LVC) – external. ☐ Single Motor Low Voltage Control (LVC) – built-in. ☐ Wireless Remote Control for LVC. ☐ Radio Frequency Remote ☐ Infrared Remote ☐ Silent Motor for sizes up to 9'x12'. ☐ SCB-200 RS-232 Serial length of case). ☐ NET-200 Ethernet-Silent Motor with Integrated LVC for sizes up to 9'x12'. ☐ Key Locking Cover Plate for 120 V Switch or LVC. ☐ IR-200 Infrared Rer Veneer Case Cover (Che Key Operated Switch for 120 V only (Note: Cannot be used)	pr:
Black "Extra Drop" to lower picture area more than normal. Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. White "Extra Drop" to lower picture area more than normal. Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. No borders (Black masking borders standard). Single Motor Low Voltage Control (LVC) – external. Single Motor Low Voltage Control (LVC) – built-in. Wireless Remote Control for LVC. Radio Frequency Remote Infrared Remote Silent Motor for sizes up to 9'x12'. Silent Motor with Integrated LVC for sizes up to 9'x12'. Key Locking Cover Plate for 120 V Switch or LVC. Key Operated Switch for 120 V only (Note: Cannot be used	or:
Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. White "Extra Drop" to lower picture area more than normal. Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. No borders (Black masking borders standard). Single Motor Low Voltage Control (LVC) – external. Single Motor Low Voltage Control (LVC) – built-in. Wireless Remote Control for LVC. Radio Frequency Remote Infrared Remote Silent Motor with Integrated LVC for sizes up to 9'x12'. Key Locking Cover Plate for 120 V Switch or LVC. Key Operated Switch for 120 V only (Note: Cannot be used Contrac Phone: Supervist Phone: Supervist Phone: Supervist Phone: Supplier Supplier Supplier Date: Supplier Date: Supplier Date: Supplier Date: Supplier Date: SCB-200 RS-232 Serial length of case). Infrared Remote	
13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. White "Extra Drop" to lower picture area more than normal. Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. No borders (Black masking borders standard). Single Motor Low Voltage Control (LVC) − external. Single Motor Low Voltage Control (LVC) − built-in. Wireless Remote Control for LVC. □ Radio Frequency Remote □ Infrared Remote Silent Motor for sizes up to 9'x12'. Silent Motor with Integrated LVC for sizes up to 9'x12'. Key Locking Cover Plate for 120 V Switch or LVC. □ Key Operated Switch for 120 V only (Note: Cannot be used Phone: Supervis	
screen. White "Extra Drop" to lower picture area more than normal. Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. No borders (Black masking borders standard). Single Motor Low Voltage Control (LVC) – external. Single Motor Low Voltage Control (LVC) – built-in. Wireless Remote Control for LVC. Radio Frequency Remote Infrared Remote Silent Motor for sizes up to 9'x12'. Silent Motor with Integrated LVC for sizes up to 9'x12'. Key Locking Cover Plate for 120 V Switch or LVC. Key Operated Switch for 120 V only (Note: Cannot be used	
White "Extra Drop" to lower picture area more than normal. Maximum total drop 13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. No borders (Black masking borders standard). Single Motor Low Voltage Control (LVC) − external. Single Motor Low Voltage Control (LVC) − built-in. Wireless Remote Control for LVC. Radio Frequency Remote Infrared Remote Silent Motor for sizes up to 9'x12'. Silent Motor with Integrated LVC for sizes up to 9'x12'. Key Locking Cover Plate for 120 V Switch or LVC. Key Operated Switch for 120 V only (Note: Cannot be used Phone: Supplier Date: Revised NET-200 RS-232 Serial length of case). IR-200 Infrared Rer Veneer Case Cover (Che Veneer Case Cover (Che Light Oak	
13' (396 Cm) including picture area. Length of extra drop required Top or Bottom of screen. No borders (Black masking borders standard). Single Motor Low Voltage Control (LVC) − external. Single Motor Low Voltage Control (LVC) − built-in. Wireless Remote Control for LVC. □ Radio Frequency Remote □ Infrared Remote Silent Motor for sizes up to 9'x12'. Silent Motor with Integrated LVC for sizes up to 9'x12'. Key Locking Cover Plate for 120 V Switch or LVC. □ Key Operated Switch for 120 V only (Note: Cannot be used Supplier Date: Revised SCB-200 RS-232 Serial length of case). □ NET-200 Ethernet-Supplier □ WC-200 Wall Control for LVC. □ Veneer Case Cover (Chemotographic Control for LVC) □ Light Oak	
Length of extra drop required Top or Bottom of screen. No borders (Black masking borders standard). Single Motor Low Voltage Control (LVC) − external. Single Motor Low Voltage Control (LVC) − built-in. Wireless Remote Control for LVC. Radio Frequency Remote Infrared Remote Silent Motor for sizes up to 9'x12'. Silent Motor with Integrated LVC for sizes up to 9'x12'. Key Locking Cover Plate for 120 V Switch or LVC. Key Operated Switch for 120 V only (Note: Cannot be used Date: Revised Revised Revised Date: Revised Revised Infrared Revised Revised Infrared Revised Infrared Revised Revised Infrared Revised Infrared Infrared Infrared Resolution Infrared Re	
No borders (Black masking borders standard). Single Motor Low Voltage Control (LVC) – external. Single Motor Low Voltage Control (LVC) – built-in. Wireless Remote Control for LVC. Radio Frequency Remote Infrared Remote Silent Motor for sizes up to 9'x12'. Silent Motor with Integrated LVC for sizes up to 9'x12'. Key Locking Cover Plate for 120 V Switch or LVC. Key Operated Switch for 120 V only (Note: Cannot be used	
Single Motor Low Voltage Control (LVC) – external. Single Motor Low Voltage Control (LVC) – built-in. Wireless Remote Control for LVC. Radio Frequency Remote Infrared Remote Silent Motor for sizes up to 9'x12'. Silent Motor with Integrated LVC for sizes up to 9'x12'. Key Locking Cover Plate for 120 V Switch or LVC. Key Operated Switch for 120 V only (Note: Cannot be used	
Wireless Remote Control for LVC. □ Radio Frequency Remote □ Infrared Remote Silent Motor for sizes up to 9'x12'. □ Silent Motor with Integrated LVC for sizes up to 9'x12'. □ Key Locking Cover Plate for 120 V Switch or LVC. □ Key Operated Switch for 120 V only (Note: Cannot be used □ Light Oak	
□ Radio Frequency Remote □ Infrared Remote □ Silent Motor for sizes up to 9'x12'. □ Silent Motor with Integrated LVC for sizes up to 9'x12'. □ Key Locking Cover Plate for 120 V Switch or LVC. □ Key Operated Switch for 120 V only (Note: Cannot be used	
□ Infrared Remote □ Silent Motor for sizes up to 9'x12'. □ Silent Motor with Integrated LVC for sizes up to 9'x12'. □ Key Locking Cover Plate for 120 V Switch or LVC. □ Key Operated Switch for 120 V only (Note: Cannot be used □ IR-200 Infrared Rer □ Veneer Case Cover (Cho	ontrol Board - built-in (adds 33/4" to
Silent Motor for sizes up to 9'x12'. Silent Motor with Integrated LVC for sizes up to 9'x12'. Key Locking Cover Plate for 120 V Switch or LVC. Key Operated Switch for 120 V only (Note: Cannot be used WC-200 Wall Contr IR-200 Infrared Rer Veneer Case Cover (Che	
Silent Motor with Integrated LVC for sizes up to 9'x12'. Key Locking Cover Plate for 120 V Switch or LVC. Key Operated Switch for 120 V only (Note: Cannot be used IR-200 Infrared Rer Veneer Case Cover (Che	
Key Locking Cover Plate for 120 V Switch or LVC. Veneer Case Cover (Checkey Operated Switch for 120 V only (Note: Cannot be used	
☐ Key Operated Switch for 120 V only (Note: Cannot be used ☐ Light Oak	
= Not operated of their restriction and the design and the second	ose nom seven standard veneers)
220 Volt (50 Hz) Motor.	
☐ Video Projector Interface Control - external. ☐ Heritage Walnut	
☐ Video Projector Interface Control - External. ☐ Video Projector Interface Control - built-in (adds 3³/₄" to ☐ Mahogany	
length of case).	
SCB-100 RS-232 Serial Control Board - external. Honey Maple	
□ NET-100 Ethernet-Serial Adapter □ Graphite case color.	
SCB-100 RS-232 Serial Control Board - built-in (adds 3 ³ / ₄ " to Black case (white stand	rd)
length of case).	1 U / .
□ NET-100 Ethernet-Serial Adapter	iuj.

CONTOUR® ELECTROL®

